




8.19 Interface

Interface

		Technical Data	Order no.
LPT interface 3HU / 6HP		1 SUB-D 25-pin female with approx. 3m connection cable and mating connector	46-7A
COM interface / RS232 3HU / 6HP		1 SUB-D 25-pin male 1 SUB-D 9-pin male both with approx. 3 m connection cable and mating connector	46-7B 46-7C
VGA interface 3HU / 6HP		1 SUB-D HD 15-pin female with approx. 3m connection cable and mating connector	46-7D
DVI-I interface 3HU / 6HP		1 female with approx. 3m connection cable and mating connector	46-7E
S-VHS interface 3HU / 6HP		1 PS / 2 Mini-DIN, 4-pin female with approx. 2 m connection cable and mating connector	46-7M
USB interface 3HU / 6HP		2 USB, type A, female with approx. 3m connection cable and mating connector	46-7F
PS/2 interface 3HU / 6HP		2 PS / 2 Mini-DIN, 6-pin female with approx. 3m connection cable and mating connector	46-7G
Audio interface 3HU / 6HP		2 Audio, Cinch, red and white, female with approx. 2.5m connection cable and mating connector	46-7H

		Technical data	Order no.
Audio interface 3HU / 6HP		1 stereo jack socket 3.5mm, stereo with approx. 3m connection cable and mating connector	46-7J
FireWire interface 3HU / 6HP		1 IEEE-1394, 6-pin with approx. 3m connection cable and mating connector	46-7K
RJ-45 interface 3HU / 6HP		1 RJ-45 connector 8-pin, female, with lettering plate, pluggable on both sides with approx. 3m patch cable	46-7L
Data socket RJ-45 3HU / 18HP		Insert plate with 1 double socket RJ45 Cat. 6 shielded non-wired	44-2D
Hollow wall socket 3HU / 18HP		Insert plate with 1 hollow wall socket for installation of an antenna, mains or telephone socket	40-1B Z004
Antenna socket 3HU / 18HP		Insert plate with 1 antenna socket for radio, TV, SAT	44-2E
IEEE 488 interface 3HU / 6HP		IEEE-488 Centronics 24-pin female with approx. 3m connection cable and mating connector	46-7N
Supply strip 3HU / 6HP		Insert plate with supply strip with 2 BNC installation jack sockets 50 Ohm can be pluggable on both sides un-wired	46-7P
ASi interface 3HU / 6HP		Insert plate interface panel ASi with 4 laboratory safety sockets 4mm yellow non-wired	46-7Q

Interface

	Technical Data	Order no.
PROFI NET interface 3HU / 6HP	 <p>Insert plate PROFI NET interface panel with 2 RJ45 connector, 8-pin, pluggable on both sides with approx. 3m patch cable</p>	46-7R
PROFI NET interface 3HU / 6HP	 <p>Insert plate PROFI BUS interface panel with 1 Sub-D adapter 9-pin, male, with mating connector female un-wired</p>	46-7S
HDMI interface 3HU / 6HP	<p>Insert plate with 1 HDMI 1.3 feed-through with 19-pin HDMI connector on both sides</p>	46-7T
Multiple interface panel 3HU / 24HP	 <p>Insert plate with 2 USB connectors, type A female 2 PS/2 Mini-DIN 6-pin connectors, female 1 Sub-D connector 9-pin male 1 Sub-D connector 15-pin HD female each with approx. 2m connection cable and mating connector 2 jack sockets, 3.5mm stereo with approx. 3m connection cable and mating connector 1 RJ45 connector, 8-pin, pluggable on both sides</p>	46-7V

Elabo also supplies modular plug-in connections for special applications. A wide variety of signals through one plug – all the way to compressed air.

Adjustable AC-supply, special insert plate

	Technical data	Order no.
<p>Adjustable AC-supply 3HU / 18HP</p> 	 <p>Eurocassette with floating, adjustable alternating current voltage 0...260V / 0.8A</p> <ul style="list-style-type: none"> 1 analogue voltmeter 0...300V 1 analogue ammeter 0...1A 1 thermal magnetic circuit breaker 1 socket without earth contact 1 illuminated rocker switch 	46-1D
<p>Antenna socket 6HU / 1WU</p>	 <p>Insert plate with antenna socket</p> <ul style="list-style-type: none"> 2 Schuko sockets 1 antenna socket TV, SAT, Radio 	32-1K
<p>Selectable pole 6HU / 1WU</p>	 <p>Insert plate with 15 non-wired laboratory safety sockets as selectable pole with labelling 1 to 15</p>	32-1U
<p>Selectable pole and emergency-off button 6HU / 1WU</p>	 <p>Insert plate with</p> <ul style="list-style-type: none"> 8 laboratory safety sockets as selectable pole with labelling 1...8 1 non-wired emergency-off mushroom button with snap-on contact and signal ring 	32-1Q
<p>Multiple interface panel 6HU / 1WU</p>	 <p>Insert plate with</p> <ul style="list-style-type: none"> 2 USB connectors, type A female 2 PS/2 Mini-DIN 6-pin connectors, female 1 Sub-D connector 9-pin male 1 Sub-D connector 15-pin HD female <p>each with approx. 2 m connection cable and mating connector</p> <ul style="list-style-type: none"> 2 jack sockets, 3.5mm stereo with approx. 3m connection cable and mating connector 2 RJ45 socket 8-pin, pluggable on both sides 	32-1U Z001